

RED CEDAR SORT SPECIFICATIONS

Code: 44

L1 20' - 27'
L2 28' - 35'
L3 36' - 40'

L SORT RED CEDAR

- A. Min. dia. 20"; Min. L 20'.
- B. Smooth appearing #3 and better surface quality.
- C. Max. defect 40 % ; Max. L deduction 20 %.
- D. Slabs with min. of 300bf of #2 & Better are acceptable.
- E. Buck off excessive L defect and broken ends.
- F. Must be suitable for producing clears.

Code: 45

SH1 12' - 27'
SH2 28' - 35'
SH3 36' - 40'

CIRCLE SH RED CEDAR

- A. Min. dia. 24"; Min. L 12'.
- B. Buck excessive butt defect.
- C. Max. defect 30% excluding checks
- D. Twist shall not exceed 3"/ft.
- E. Slabs must have a min. of 400bf
- F. Must be merchantable for producing lumber recovery.

Code: 46

SH1 12' - 27'
SH2 28' - 35'
SH3 36' - 40'

SH RED CEDAR

- A. Dia. 8" thru 23", approx. 5 % = 6" to 7" allowed by piece count; Min. L 12'.
- B. Buck excessive end defect; No excessive twist.
- C. Slabs must have a min. of 200bf.
- D. Must be merchantable for producing lumber recovery.
- E. DOUBLE WRAP all bundles!! Max. 25 ton bundles.

Code: 41

C1 12' - 27'
C2 28' - 35'
C3 36' - 40'

C SORT RED CEDAR

- A. Min. diam. 20"; Min. L 12'
- B. Max defect 66%
- C. Scribner Scale

Sort Specifications are subject to change without notice.